

TECHNICAL SPECIFICATION

ZINTRA ACOUSTIC PANEL 3mm

| | |
|----------------------------|---|
| Product | Zintra Acoustic 3mm panel |
| Description | 100% recyclable polyester. Contains 60% post-consumer recycled PET. Matte finish. |
| Weight | 2.4kg per m2 (approx 2kg per sheet) |
| Panel Size | 2800mm x 1225mm x 3mm |
| Acoustic Rating | aw 0.15 / NRC 0.15 |
| Fire Rating | Euroclass B |
| Installation | Adhere to substrate with Tekfix Plus or suitable heavy duty wallcovering adhesive. |
| Application | Indoor areas only. |
| Colourfastness | In accordance with AATCC 16.3 option 3, colour change at 20 AFU was 4.5. |
| Maintenance | Vacuum to remove dust. Surface can be disinfected by spraying with diluted bleach solution (4 teaspoons per 0.95 litres water). Wipe off surface moisture. |
| Health & Safety | This product is classified as non-hazardous and therefore does not require any special handling. This product does not require special labelling. |
| Handling/Storage | Zintra acoustic panels must be stored in a cool, dry, well ventilated area, out of direct sunlight and away from heat sources. During storage keep covered (eg with polythene sheet) at all times. Panels should be stored horizontally. Pallets should not be stacked. |
| Fire Fighting | Any extinguishing media are suitable. Wear self contained breathing apparatus, protective clothing and full face mask. Fumes should be ventilated immediately due to possible liberation of noxious gases. |
| Ecological | This product is 100% recyclable polyester. Zintra is not bio-degradable. Dispose of in accordance with Local Authority regulations or via an authorised contractor. |